



Enduraline 472X

Premium Pack Off Grease for Greaseless Wireline

TECHNICAL DATA SHEET | ENDURALINE 472X

Description

Enduraline 472X is a Premium Pack Off Grease for Greaseless Wirelines formulated with rust, corrosion, and extreme pressure additives.

Enduraline 472X has cohesive properties that coat the plastic sheath of the wireline to ensure optimal coverage by the lubricant and prevent corrosion damage. This protection decreases lubrication frequency and reduces downtime.

Enduraline 472X uses a proprietary blend of corrosion inhibitors, friction modifiers, and antioxidants. The corrosion inhibitors in the blend form a protective layer to insulate the cable from any H₂S and CO₂ present in the well and any other harmful substances present downhole. The friction modifiers and anti-oxidants extend the life of the wireline, and the added grease continues providing protection while the job is in progress.

Application

Enduraline 472X is recommended for “greaseless wireline” applications as a pack off grease for protecting the plastic sheath covering the wireline cable.

SPECIFICATIONS

Color	Green
Texture	Tacky Grease
Density, Lbs/Gal @ 77°F (25°C)	7.84
Specific Gravity @ 77°F (25°C)	0.7822
NLGI Grade	0
Dropping Point (°F/°C)	300/149
Oil Separation	10.19%
4-Ball Wear Scar (mm)	0.54
4-Ball EP Weld load (kg)	400
Shelf Life (Unopened Container)	4 Years